



Shanghai Ruonan-Power Co., Ltd.



63308ZZ Bearing 2D drawings and 3D CAD models

40,000 mm x 90,000 mm x 36,500 mm NTN
63308ZZ deep groove ball bearings

Bearing No. 63308ZZ

Size	40x90x36.500 mm
Bore Diameter	40,000 mm
Outer Diameter	90,000 mm
Width	36,500 mm
d	40,000 mm
D	90,000 mm
B	36,500 mm
C	36,500 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359582901
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	40MM Bore; 90MM



Shanghai Ruonan-Power Co., Ltd.

	Outside Diameter; 36.53MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; S
Other Features	Deep Groove Cartridge Type Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	2.06
Outer Race Width	1.438 Inch 36.53 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Bore	1.575 Inch 40 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	40 mm
static load capacity:	24000 N
outside diameter:	90 mm
precision rating:	ISO Class 0
overall width:	36.5 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	36.50 mm



Shanghai Ruonan-Power Co., Ltd.

snap ring included:	Without Snap Ring
outer ring width:	36.50 mm
internal clearance:	CN
maximum rpm (grease):	7800 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1.5 mm
dynamic load capacity:	40500 N
manufacturer product page:	Click here