



S71918 CD/P4A Bearing 2D drawings and 3D CAD models

90 mm x 125 mm x 18 mm SKF S71918
CD/P4A angular contact ball bearings

Bearing No. S71918 CD/P4A

Size	125x90x18 mm
Bore Diameter	125 mm
Outer Diameter	90 mm
Width	18 mm
d	90 mm
D	125 mm
B	18 mm
d ₁	100.8 mm
d ₂	100.8 mm
D ₂	117.1 mm
r _{1,2} - min.	1.1 mm
r _{3,4} - min.	0.6 mm
a	23.5 mm
d _a - min.	96 mm
d _a - max.	100.2 mm
d _b - min.	96 mm
d _b - max.	100.2 mm
D _a - max.	119 mm
D _b - max.	121 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	47.5 kN
Basic static load rating - C ₀	51 kN
Fatigue load limit - P _u	2.1 kN



Shanghai Ruonan-Power Co., Ltd.

Limiting speed for grease lubrication	9500 r/min
Ball - D_w	11.112 mm
Ball - z	26
Calculation factor - f_0	16.3
Preload class A - G_A	180 N
Preload class B - G_B	360 N
Preload class C - G_C	720 N
Preload class D - G_D	1440 N
Calculation factor - f	1.23
Calculation factor - f	1
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.04
Calculation factor - f_{2C}	1.09
Calculation factor - f_{2D}	1.15
Calculation factor - f_{HC}	1
Preload class A	94 N/micron
Preload class B	129 N/micron
Preload class C	183 N/micron
Preload class D	268 N/micron
d_1	100.8 mm
d_2	100.8 mm
D_2	117.1 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	96 mm
d_a max.	100.2 mm
d_b min.	96 mm
d_b max.	100.2 mm
D_a max.	119 mm
D_b max.	121 mm



Shanghai Ruonan-Power Co., Ltd.

r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	47.5 kN
Basic static load rating C_0	51 kN
Fatigue load limit P_u	2.08 kN
Attainable speed for grease lubrication	9500 r/min
Ball diameter D_w	11.112 mm
Number of balls z	26
Preload class A G_A	180 N
Static axial stiffness, preload class A	94 N/ μ m
Preload class B G_B	360 N
Static axial stiffness, preload class B	129 N/ μ m
Preload class C G_C	720 N
Static axial stiffness, preload class C	183 N/ μ m
Preload class D G_D	1440 N
Static axial stiffness, preload class D	268 N/ μ m
Calculation factor f	1.23
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.04
Calculation factor f_{2C}	1.09
Calculation factor f_{2D}	1.15
Calculation factor f_{HC}	1
Calculation factor f_0	16.3
Mass bearing	0.57 kg