



BK 1612 Bearing 2D drawings and 3D CAD models

SKF BK 1612 cylindrical roller bearings

Bearing No. BK 1612

Size	22x16x12 mm
Bore Diameter	22 mm
Outer Diameter	16 mm
Width	12 mm
F_w	16 mm
D	22 mm
C	12 mm
C_1 - min.	9.3 mm
r - min.	0.8 mm
Basic dynamic load rating - C	7.4 kN
Basic static load rating - C_0	9.8 kN
Fatigue load limit - P_u	1.1 kN
Reference speed	14000 r/min
Limiting speed	16000 r/min
Mass bearing	0.014 kg
Inner ring IR series	IR 12x16x13
Radial shaft seal with a low cross-sectional height, single lip	G 16x22x3
Category	Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.014
Product Group	B04144
F_w	16 mm



Shanghai Ruonan-Power Co., Ltd.

C ₁ min.	9.3 mm
r min.	0.8 mm
Basic dynamic load rating C	7.37 kN
Basic static load rating C ₀	9.8 kN
Fatigue load limit P _u	1.12 kN
Designation bearing	BK 1612
Radial shaft seal with a low cross-sectional height, double lip	SD 16x22x3